



## POW'R-WRAP™ TIES

A stainless steel tie that is dependable, easy to apply and can be used in a broad range of fastening, securing and sealing applications.

- T304 1/4" stainless steel for exceptional corrosion resistance in outdoor environments
- Available in lengths of 10" up to 35"
- Smooth seal design for gap free contact
- Minimum loop strength of 400 lbs.
- Tensions, cuts and locks for quick and easy application
- For the securement of ducting, tags, hoses, cable bundles and constant velocity boots

### INDUSTRIES

- Agriculture
- Automotive
- Bridge & Tunnels
- Chemical processing and refining
- Construction
- Oil and Gas
- Offshore Platforms
- Marine
- Mining
- Municipalities
- Telecommunications
- Utilities

### STAINLESS STEEL

Item No.	Width		Length		Thickness		Qty/ Bag	Carton Weight		Hose OD*
	inch	mm	inch	mm	inch	mm		lbs	kg	inch
HBPW211	1/4	6.35	10	254.0	0.015	0.38	100	1.2	0.6	2
HBPW212	1/4	6.35	16.5	419.1	0.015	0.38	100	1.8	0.9	4
HBPW213	1/4	6.35	22.5	571.5	0.015	0.38	100	2.6	1.2	6
HBPW214	1/4	6.35	29	736.6	0.015	0.38	100	3.3	1.5	8
HBPW215	1/4	6.35	35	889.0	0.015	0.38	100	3.9	1.8	10

\*Recommended Hose OD's for single wrap application/installation

### RELATED PRODUCT



#### ID Tags

The tags are .015" and can be fastened with Strapbinder Pow'r-Wrap ties.

Item No.	Description	Material	Qty/ Box	Weight	
				lbs	kg
ST750350	3/4" X 3-1/2"	T304	100	0.6	0.30
ST750200	3/4" X 2"	T316	100	0.5	0.20
ST150250	1-1/2" X 2-1/2"	T316	100	1.4	0.67

**IDEALTRIDON.COM | PROVEN DESIGNS, BILLIONS OF TIMES**

GLOBAL HEADQUARTERS

8100 TRIDON DRIVE SMYRNA, TN USA 800.251.3220 | 615.459.5800

USA | CANADA | MEXICO | CHINA | JAPAN | POLAND | ITALY | INDIA

